

DUSK TO DAWN (MDD01)

DESCRIPTION

Multi-purpose dusk-to-dawn LED luminaire delivers ultra-efficient LED lighting with a low total cost of ownership and a quick return on investment. It features a power door for easy maintenance and 3G vibration rated construction. While its lightweight design, tool-less entry, and easy installation make dusk-to-dawn luminaire an ideal solution for any contractor.

SPECIFICATION FEATURES

Overview

- Initial Delivered Lumens: 6,350-9,600lm
- CRI: ≥ 70
- CCT: Optioal 4000K and 5000Kt
- Mounting: Mounts directly to wall surface or to pole with mounting arm (accessory sold separately)
- Operating Minimum: -40°C (-40°F)
- Lifespan: Estimated >50,000 Hours
- Power Factor: ≥ 0.9
- Total Harmonic Distortion: ≤20%
- Limited Warranty: 5 Years
- Replaces up to 175W MH

Construction

- Durable, die-cast aluminum housing dark bronze polyester powder-coat finish
- Twist-lock photocell included

Recommended use

- General Area Illumination
- Entryways & Pathways
- Yards & Loading Docks

Electrical

- Input Voltage: 120-277V
- Operating Temperature Range: -40°C - + 45°C (-40°F - + 113°F)

Listing

- cULus Listed
- Suitable for wet locations



ORDERING GUIDE

Example: ST 45W 27V XXX A YY

Fixture Type	Wattage	Voltage	CCT	Series	Finish	Photocell (Option)
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
ST Street Light	45 45W 70 70W	27V 120-277V	40K 4000K 50K 5000K	A A Series	D Dark Bronze B Black W White SG Silver Gray	P0 120-277V Photocell Blank Without Photocell



