

DATA SHEET: LED PL LIGHT BYPASS MODEL 360 DEGREES


Our Patriot LED BYPASS Model PL LIGHT 360 degrees GX24-4pin and G24-2pin are ballast-bypass ready for easy installation and are backed with our industry-leading 100,000-hour rated lamp life and 10-year warranty. See Ordering Model table below for our BAA compliant products. Contact us for pricing or more information.

PRODUCT BENEFITS

- 50% - 70% energy saving than CFL.
- BALLAST BYPASS ONLY
- No mercury, no UV and infrared in beam.
- Isolated Power Supply inside, it's more safe and better for heat dissipation.
- Extruded aluminum is good at heat dissipation, surface temperature usually stay below 65°.
- Surface of aluminum was protected with being oxygenated.
- We use quality Rubycon capacitors.
- Service time is up to 100,000 hours.
- Warranty 5 year (10 year optional).




BEAM ANGLE



Patriot LED Light Distribution

CAN DECREASE ENERGY USAGE BY



vs. Similar Fluorescent Lamps

WARRANTY



Our Industry-Leading 10-Year Limited Warranty Guarantees Unsurpassed Quality

TECHNICAL DATA

- Wattage: 4W, 6W, 9W, 12W
- Operating Temperature: -20°C to 45°C
- Beam Angle: 360°
- LED Source: 2835
- Luminous: 100LM/W-130LM/W
- Dimmable: No
- Power Factor: >0.9
- Certificates: CE, ROHS, ETL

ORDERING MODEL

PATRIOT TUBE	LAMP BASE	CRI	VOLTAGE	WATTAGE	BEAM ANGLE	WORKING HOURS
PT	-GXxx-Xw	>80	120-277V 50/60Hz	4W, 6W 9W, 12W	360°	100,000 hours
Product Code: example						
PT-Gxxx--6W-BYP - SEE BELOW FOR BASE OPTIONS						



PRODUCT SPECIFICATION

Product No.	BAA/TAA Option*	Rated Lamp Wattage	Dimmable	Lamp Base Voltage	Input Voltage	Color Temp (K)	Luminous	LED Source	Rated Life (Hours)	Led Quantity	Power Factor
LED PL LIGHT BYPASS MODEL 360 DEGREES											
PT-Gxxx-4W	Yes	4W	NO	GX24-4pin / G24-2pin	120-277V / 50/60Hz	Warm White / Pure White / Cool White	520-680LM	2835SMD	100,000	48PCS	> 0.9
						2700K-300k / 4000-4500K / 6000-6500K					
PT-Gxxx-6W	Yes	6W	NO	GX24-4pin / G24-2pin	120-277V / 50/60Hz	Warm White / Pure White / Cool White	660-780LM	2835SMD	100,000	48PCS	> 0.9
						2700K-300k / 4000-4500K / 6000-6500K					
PT-Gxxx-9W	Yes	9W	NO	GX24-4pin / G24-2pin	120-277V / 50/60Hz	Warm White / Pure White / Cool White	880-1040LM	2835SMD	100,000	60PCS	> 0.9
						2700K-300k / 4000-4500K / 6000-6500K					
PT-Gxxx-12W	Yes	12W	NO	GX24-4pin / G24-2pin	120-277V / 50/60Hz	Warm White / Pure White / Cool White	1320-1560LM	2835SMD	100,000	72PCS	> 0.9
						2700K-300k / 4000-4500K / 6000-6500K					

PHYSICAL DATA

Product No.	Product Size (φ*L)	Lamp Base	Material	Applications	Package	Product Weight (kg)	Carton Size (cm) Qty/Ctn, Gross Weight (kg)	Certification
LED PL LIGHT BYPASS MODEL 360 DEGREES								
PT-Gxxx-4W	φ33X99mm, φ33X105mm	GX24-4pin G24-2pin	Extruded aluminum heat sink	Indoor lighting	White box/ customized	0.12 KG	20*38*20cm (L*W*H) 100PCS, 15kg	ETL ROHS EMC
PT-Gxxx-6W	φ33X99mm, φ33X105mm	GX24-4pin G24-2pin	Extruded aluminum heat sink	Indoor lighting	White box/ customized	0.12 KG	20*38*20cm (L*W*H) 100PCS, 15kg	ETL ROHS EMC
PT-Gxxx-8W	φ33X116mm, φ33X122mm	GX24-4pin G24-2pin	Extruded aluminum heat sink	Indoor lighting	White box/ customized	0.17 KG	20*38*25cm (L*W*H) 100PCS, 20KG	ETL ROHS EMC
PT-Gxxx-12W	φ33X116mm, φ33X122mm	GX24-4pin G24-2pin	Extruded aluminum heat sink	Indoor lighting	White box/ customized	0.23 KG	20*38*36cm (L*W*H) 100PCS, 25KG	ETL ROHS EMC

We have following lamps. Please check availability before order.

