

# DATA SHEET: 360 DEGREES G24Q-4PIN/2PIN LED PL LIGHT


Our 360 degrees G24Q-4pin/2pin are ballast ready for easy installation and are backed with our industry-leading 50,000-hour rated lamp life and 10-year warranty. See Ordering Model table below for our BAA compliant products. Contact us for pricing or more information.

## PRODUCT BENEFITS

- 50% - 70% energy saving than CFL
- No mercury, no UV and infrared in beam.
- Isolated Power Supply inside, it's more safe and better for heat dissipation.
- Extruded aluminum is good at heat dissipation, surface temperature usually stay below 65°
- Surface of aluminum was protected with being oxy-genated.
- We use quality Rubycon capacitors.
- Service time is upto 50,000 hours.
- Warranty 5 year (10 year optional).




### BEAM ANGLE



Patriot LED Light Distribution

### CAN DECREASE ENERGY USAGE BY



vs. Similar Fluorescent Lamps

### WARRANTY



Our Industry-Leading 10-Year Limited Warranty Guarantees Unsurpassed Quality

## TECHNICAL DATA

- Wattage: 4W, 6W, 9W, 12W
- Beam Angle: 360°
- Led Source: 5730
- Luminous: 990-1080
- LED quantity: 20 pcs
- Dimmable: No
- Power Factor: >0.9
- Certificates: CE, ROHS, EMC

## ORDERING MODEL

PATRIOT TUBE	LAMP BASE	CRI	VOLTAGE	WATTAGE	BEAM ANGLE	WORKING HOURS
PT	G24Q 4pin / 2pin	>80	AC120-277V 50/60Hz	4W 6W 9W 12W	360°	50,000 hours
Product Code: example						
PT-T-G24Q-9						



Beam angle 360° = T

## PRODUCT SPECIFICATION

Product No.	BAA/TAA Option*	Rated Lamp Wattage	Dimmable	Lamp Base Voltage	Input Voltage	Color Temp (K)	Luminous	LED Source	Rated Life (Hours)	Operating Temp. (°F)	PF
<b>LED PL LIGHT HYBRID MODEL 360 DEGREES (GX24-4PIN, G24-2PIN)</b>											
PT-T-G24Q-4	Yes	4W	NO	G24Q - 4pin/2pin	AC120-277V 50/60Hz	Warm White / Pure White / Cool White	540	5730	50,000	20°C to 45°C	> 0.9
						2800 - 3200K   4000 - 4500K   6000 - 6500K					
PT-T-G24Q-6	Yes	6W	NO	G24Q - 4pin/2pin	AC120-277V 50/60Hz	Warm White / Pure White / Cool White	810	5730	50,000	20°C to 45°C	> 0.9
						2800 - 3200K   4000 - 4500K   6000 - 6500K					
PT-T-G24Q-9	Yes	9W	NO	G24Q - 4pin/2pin	AC120-277V 50/60Hz	Warm White / Pure White / Cool White	990-1080	5730	50,000	20°C to 45°C	> 0.9
						2800 - 3200K   4000 - 4500K   6000 - 6500K					
PT-T-G24Q-9	Yes	12W	NO	G24Q - 4pin/2pin	AC120-277V 50/60Hz	Warm White / Pure White / Cool White	1500	5730	50,000	20°C to 45°C	> 0.9
						2800 - 3200K   4000 - 4500K   6000 - 6500K					

## PHYSICAL DATA

Product No.	Material Usage	Application	Package	Corton Size (cm)	Qty / Ctn Gross Weight (kg)	Housing color	LED QTY	Certification
<b>LED PL LIGHT HYBRID MODEL 360 DEGREES (GX24-4PIN, G24-2PIN)</b>								
PT-T-G24Q-4	Extruded aluminum heat sink	Indoor Lighting	Whitebox Customized	25*22*30cm (L * W * H)	50 PCS 7 KG	White+Grey		CE ROHS EMC
PT-T-G24Q-6	Extruded aluminum heat sink	Indoor Lighting	Whitebox Customized	25*22*30cm (L * W * H)	50 PCS 7 KG	White+Grey		CE ROHS EMC
PT-T-G24Q-9	Extruded aluminum heat sink	Indoor Lighting	Whitebox Customized	25*22*30cm (L * W * H)	50 PCS 7 KG	White+Grey	20 PCS	CE ROHS EMC
PT-T-G24Q-12	Extruded aluminum heat sink	Indoor Lighting	Whitebox Customized	25*22*30cm (L * W * H)	50 PCS 7 KG	White+Grey		CE ROHS EMC

We have following lamps. Please check availability before order.

